

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) A method wherein multiple input signals are subjected to a combination process of adaptive beamforming and adaptive echo cancelling, characterized in that for each of the input signals an individual processing history of adaptive echo cancelling data is kept and combined with current adaptive beamforming data.

2. (Original) The method according to claim 1, characterized in that the combined adaptive processing is devised such that each of the respective input signals is running through a parallel path containing an accustic path and a beamformer path, whereafter signals in the parallel paths are summed and processed.

3. (Original) The method according to claim 1 or 2, characterized in that adaptive beamforming concerns filtering or weighting of the input signals.

4. (Previously presented) An audio processing device comprising parallel acoustic paths for providing respective input

signals, the acoustic paths are connected in series to beamformer paths, the device comprises an adaptive beamformer and an adaptive echo canceller, characterized in that the adaptive echo canceller is provided with storage means for storing in relation to every input signal, individual processing histories of adaptive echo cancelling data for combination with current adaptive beamforming data, the beamformer and canceller being configured for simultaneously adaptive operation.

5. (Original) The audio processing device according to claim 4, characterized in that the audio processing device is devised such that each of the respective input signals is running through a parallel path containing an acoustic path and a beamformer path, whereafter signals in the parallel paths are summed and processed.

6. (Original) The audio processing device according to claim 4 or 5, characterized in that the adaptive beamformer is a filtered and/or weighted beamformer.

7. (Previously presented) The audio processing device according to claim 4 or 5, characterized in that the adaptive echo canceller comprises a Time Domain Adaptive Filter (TDAF), or a Frequency Domain Adaptive Filter (FDAF).

8. (Currently amended) An audio processing device comprising parallel acoustic paths for providing respective input signals, the acoustic paths are connected in series to beamformer paths, the device comprises an adaptive beamformer and an adaptive echo canceller, characterized in that the adaptive echo canceller is provided with storage means for storing in relation to every input signal, individual processing histories of adaptive echo cancelling data for combination with current adaptive beamforming data, characterized in that the adaptive ~~filter~~ echo canceller comprises a first section for calculating at least one loudspeaker input spectrum and a part of normalized update data, and a second section for performing convolution and calculating echo cancelling coefficient update data.

9. (Currently amended) The audio processing device according to claim 8, characterized in that the second ~~adaptive echo canceller~~ section comprises an adaptive summing filter having an input for receiving beamformer filtering or weighting coefficients, the summing filter comprising the storage means for storing in relation to every input signal, individual processing histories of adaptive echo cancelling data for combination with current adaptive beamforming data.

10. (Previously presented) A communication device, comprising:
 at least one loudspeaker, multiple microphones for
 providing respective inputs signals, which microphones are coupled
 to the at least one loudspeaker through acoustic paths, an adaptive
 beamformer and an adaptive echo canceller, characterized in that
 the adaptive echo canceller is provided with storage means for
 storing in relation to every input signal an individual processing
 history of adaptive echo cancelling data for combination with
 current adaptive beamforming data, the beamformer and canceller
 being configured for simultaneously adaptive operation.

11. (Previously presented) The method of claim 1, wherein, the
 beamforming and cancelling are simultaneous.